



Комплексное решение для багетных мастерских

SHH-5

SPECIFICATIONS:

Base Material:	100%polyester
Surface Finish:	waterbased Matte
Weight(g/m2):	280±5 gsm
Width:	24"/36"/42"/44"/50"/60"/72"
Length:	18m/30m/50 or Customized
Core:	2"/3"

PRODUCT FEATURES

Superior tear resistance
Bright white Matte surface
Applied without wrinkles
Perfect color control
Clear texture

APPLICATION:

Office printing, artistic giclee prints, advertising, exhibition layout, home decoration.

COMPATIBILITY INK AND PRINTER:

Ink:	Printer:
DYE	Most aqueous printing systems
PIGMENT	Especially Hp, Epson, Canon, Rolan, etc
UV	

PRODUCT GUIDELINE:

Printing Condition

Dry time will vary depending on ink type.
Suitable printing condition:
Temperature 15-30°C (59~86(°F)/Humidity 30~60%.

Storage

It is recommended to store in the closed original packing in a cool and dry environment.
Temperature 10~27°C (50~80°F), Relative Humidity 50%RH.
One year stored in the recommended condition.

NOTE

The information described above is our test criteria, All material should be tested by customers to determine the suitable products. Printer or ink change may affect printing results.